


380-415V 3N~ 50/60Hz



STROMVERSORGUNG/POWER SUPPLY	380-415V 3N~ 50/60Hz
M = ANSCHLUSSKLEMME/TERMINAL CLAMP	FV122 6 POLI - 40 A - 450 V
BF = SCHALTER F. OFEN/SWITCH F. OVEN	49.44215.700+49.21015.705 0,1,2,3 POS 16A 250V T150 EGO 55.32574.110
S1 = SICHERHEITSTHERM./SAFETY THERM.	T=360°C -25K 20(4)A 400V EGO 55.34052.811
T1 = THERMOSTAT/THERMOSTAT	16A 250V T150 [60°C - 295°C]
LV = KONTROLLAME GRÜN/GREEN IND. LIGHT	SIGNAL LUX Mod 21.3 230V (T120) Silicon Leads
LR = KONTROLLAME ROT/RED IND. LIGHT	SIGNAL LUX Mod 21.3 230V (T120) Silicon Leads
LB = KONTROLLAME WEIß/WHITE IND. LIGHT	SIGNAL LUX Mod 21.3 230V (T120) Silicon Leads
RF1 = HEIZKÖRPER F. BACKOFEN OBEN/ HEATING EL. OVEN TOP	3300 watt (1x) 230V 14.5 A
RF2 = HEIZKÖRPER F. BACKOFEN UNTEN/ HEATING EL. OVEN BOTTOM	2300 watt (1x) 230V 10.5 A
KABEL/CABLE	CAVO H05SJ-K Section 1.5 mm ²
KABEL F. KONTROLLLAMPE/CABLE F. IND. LIGHT	CAVO H05SJ-K Section 0.75 mm ²