

Freezing cabinet with white painted steel casing

236086

External housing made of white coated steel. Fan assisted cooling. Rear external wall and bottom made of galvanised sheet metal. Interior made of ABS plastic. Thick cyclopentane foam insulation (C5H10) (up to 65 mm), depending on the model, for greater temperature stability inside the cabinet. Highly accurate digital thermostat makes it possible to precisely determine storage temperature. Adjustable shelves with a load capacity of 30 kg each, provided that the weight in the cooling display cabinet is distributed evenly. Fixed shelves with freezing system components, with a load capacity of 25 kg each, provided that the weight in the freezing display cabinet is distributed evenly. Additional shelf at the bottom of the chamber to increase storage space (selected models only – see table). Electromechanical control with electronic display for indicating set and actual temperature. With 2 feet at the front allow for limited height adjustment and 2 castors at the back, ideal for moving the cabinet (only cabinets with the capacity of 400 and 600 l). Self-closing doors to reduce electricity consumption. Locking doors (with a key).

Fixed shelves 6x452x412 mm. Opening door alarm.



HENDI B.V.
Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.
ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH
Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.
Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA
5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.
Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu

Specifications

Voltage	: 230
Temp range from (°C)	: -18°C
Temp range to (°C)	: -23°C
Unit temperature	: Celsius
Refrigerant	: R290
Insulation thickness (mm)	: 60
Climate class	: 3 (25°C 60% RH)
Reversible door	: Yes
Electrician needed	: No

Marketing Packed per	: 1
Length (mm)	: 600
Width (mm)	: 646
Height (mm)	: 1875
Internal length (mm)	: 480
Internal width (mm)	: 448
Internal height (mm)	: 1611
Maximum volume (L)	: 400
Power (input) (W)	: 322
Measurements	: 600x646x(H)1875
Colour	: White

Transport specifications

EAN	: 8711369236086
Intrastat code	: 84185011
Gross weight (kg)	: 73
Net weight (kg)	: 63
Sales units per pallet	: 1
Plastic packaging (gram)	: 575

HENDI B.V.

Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.

ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH

Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA

5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.

Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu